

DECLARATION OF PERFORMANCE

N. CPR-ES2/0015

1 Unique identification code of the product-type	DESMOPOL DW
2 Intended uses	Two-component polyurethane coating for intended use in concrete surface protection by protection against ingress; moisture control and increasing resistivity; physical resistance; chemical resistance methods
3 Manufacturer	TECNOPOL SISTEMAS, S.L.U. Finlàndia, 33 08520 Les Franqueses del Vallés – Barcelona-Spain www.tecnopolgroup.com – t. +34 935682111
4 Systems of AVCP	System 2+ System 3 (for reaction to fire)
5 Harmonized standards	EN 1504-2:2004
Notified bodies	The notified body LGAI TECHNOLOGICAL CENTER, S. A./Applus, N. 0370, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control. The notified laboratory CSI S.p.A N. 0497, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.
6 Performances declared	
Essential characteristics	Performances
Abrasion resistance:	Weight loss < 3000 mg
Permeability to CO ₂ :	Sd > 50 m
Water vapor permeability:	Class II
Capillary absorption and permeability to water:	< 0,1 kg/m ² ·h ^{0.5}
Resistance to thermal shock:	≥ 1,5 N/mm ²
Resistance to severe chemical attack:	Reduction hardness ≤ 50% (Shore D)
Group 9,	Class II (Slight loss of gloss)
Group 10,12	Class II
[Potassium Hydroxide 20%vol]	Class II (Loss of gloss)
Crack bridging ability	A4 (-10°C), B4,1(23°C)
Impact resistance:	Class II
Adhesion strength by pull-off test:	≥ 1,5 N/mm ²
Reaction to fire:	Class E
Dangerous substances:	NPD

Legend for Resistance to severe chemical attack: groups numbers and related descriptions as per EN 13529	
Group 9:	Aqueous solutions of organic acids up to 10%
Group 10:	Inorganic acids up to 20% and salts with acid hydrolysis in aqueous solution (pH < 6) except for the hydrofluoric acid and oxidizing acids and their salts
Group 12:	Solutions of inorganic non-oxidizing salts with pH = 6 - 8

7 REACH information	the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that TECNOPOL makes available on the website along with this current Declaration of Performance
------------------------------	---

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **David Pont – Technical Service Manager**



Les Franqueses del Vallès,

26/03/2020



DoP in Pdf format are available in the Tecnopol website.

<i>Revision 0 notes:</i>	<i>First issue</i>
--------------------------	--------------------

 0370, 0497	 TECNOPOL SISTEMAS, S.L.U., Finlàndia, 33 08520 Les Franqueses del Vallés – Barcelona-Spain – www.tecnopolgroup.com																												
<p style="text-align: center;">20 CPR-ES2/0015 DESMOPOL DW</p> <p style="text-align: center;">Two-component polyurethane coating for intended use in concrete surface protection by protection against ingress; moisture control and increasing resistivity; physical resistance; chemical resistance methods</p>																													
<table style="width: 100%; border: none;"> <tr> <td style="width: 40%;">Abrasion resistance:</td> <td>Weight loss < 3000 mg</td> </tr> <tr> <td>Permeability to CO₂:</td> <td>Sd > 50 m</td> </tr> <tr> <td>Water vapor permeability:</td> <td>Class II</td> </tr> <tr> <td>Capillary absorption and permeability to water:</td> <td>< 0,1 kg/m²·h^{0.5}</td> </tr> <tr> <td>Resistance to thermal shock:</td> <td>≥ 1,5 N/mm²</td> </tr> <tr> <td>Resistance to severe chemical attack:</td> <td>Reduction hardness ≤ 50% (Shore D)</td> </tr> <tr> <td style="padding-left: 40px;">Group 9,</td> <td>Class II (Slight loss of gloss)</td> </tr> <tr> <td style="padding-left: 40px;">Group 10,12</td> <td>Class II</td> </tr> <tr> <td style="padding-left: 40px;">[Potassium Hydroxide 20%vol]</td> <td>Class II (Loss of gloss)</td> </tr> <tr> <td>Crack bridging ability</td> <td>A4 (-10°C), B4,1(23°C)</td> </tr> <tr> <td>Impact resistance:</td> <td>Class II</td> </tr> <tr> <td>Adhesion strength by pull-off test:</td> <td>≥ 1,5 N/mm²</td> </tr> <tr> <td>Reaction to fire:</td> <td>Class E</td> </tr> <tr> <td>Dangerous substances:</td> <td>NPD</td> </tr> </table>		Abrasion resistance:	Weight loss < 3000 mg	Permeability to CO ₂ :	Sd > 50 m	Water vapor permeability:	Class II	Capillary absorption and permeability to water:	< 0,1 kg/m ² ·h ^{0.5}	Resistance to thermal shock:	≥ 1,5 N/mm ²	Resistance to severe chemical attack:	Reduction hardness ≤ 50% (Shore D)	Group 9,	Class II (Slight loss of gloss)	Group 10,12	Class II	[Potassium Hydroxide 20%vol]	Class II (Loss of gloss)	Crack bridging ability	A4 (-10°C), B4,1(23°C)	Impact resistance:	Class II	Adhesion strength by pull-off test:	≥ 1,5 N/mm ²	Reaction to fire:	Class E	Dangerous substances:	NPD
Abrasion resistance:	Weight loss < 3000 mg																												
Permeability to CO ₂ :	Sd > 50 m																												
Water vapor permeability:	Class II																												
Capillary absorption and permeability to water:	< 0,1 kg/m ² ·h ^{0.5}																												
Resistance to thermal shock:	≥ 1,5 N/mm ²																												
Resistance to severe chemical attack:	Reduction hardness ≤ 50% (Shore D)																												
Group 9,	Class II (Slight loss of gloss)																												
Group 10,12	Class II																												
[Potassium Hydroxide 20%vol]	Class II (Loss of gloss)																												
Crack bridging ability	A4 (-10°C), B4,1(23°C)																												
Impact resistance:	Class II																												
Adhesion strength by pull-off test:	≥ 1,5 N/mm ²																												
Reaction to fire:	Class E																												
Dangerous substances:	NPD																												

Note:

TECNOPOL SISTEMAS S.L.U supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.