

DECLARATION OF PERFORMANCE

N. CPR-ES2/0021

1 Unique identification code of the product-type	MASTIC PU
2 Intended uses	Polyurethane mastic for caulking exterior and interior joints in pedestrian areas, cold weather applications
3 Manufacturer	TECNOPOL SISTEMAS, S.L.U. Finlàndia, 33 08520 Les Franqueses del Vallés – Barcelona-Spain www.tecnopolgroup.com – t. +34 935682111
4 Systems of AVCP	System 3
5 Harmonized standards	EN 15651-4: PW EXT-INT CC
Notified bodies	The notified laboratory GINGER CEBTP N. 0074, carried out the assessment of the performance (reaction to fire) and initial tests on the basis of testing on samples taken by the manufacturer.
6 Performances declared	
Essential characteristics	Performances
Fire reaction:	Euroclass E
Water and air waterproofing:	
Loss of volume	<10%
Flow resistance:	< 3mm.
Durability:	Pass
Adhesion/cohesion tensile deformation properties maintained in water immersion at 23°C:	No break
Adhesion/cohesion tensile deformation properties maintained at -30°C:	No break

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by **David Pont – Technical Service Manager**



Les Franqueses del Vallés,

18/07/2021



DoP in Pdf format is available on the Tecnopol website.

<i>Revision 0 notes:</i>	<i>First issue</i>
--------------------------	--------------------

 0074	 TECNOPOL SISTEMAS, S.L.U., Finlàndia, 33 08520 Les Franqueses del Vallés – Barcelona-Spain – www.tecnopolgroup.com																											
21 CPR-ES2/0021 EN 15651-4: PW EXT-INT CC MASTIC PU Polyurethane mastic for caulking exterior and interior joints in pedestrian areas, cold weather applications																												
<table style="width: 100%; border: none;"> <tr> <td style="width: 30%;"></td> <td>Fire reaction:</td> <td>Euroclass E</td> </tr> <tr> <td></td> <td>Water and air waterproofing:</td> <td></td> </tr> <tr> <td></td> <td>Loss of volume</td> <td><10%</td> </tr> <tr> <td></td> <td>Flow resistance:</td> <td>< 3mm.</td> </tr> <tr> <td></td> <td>Durability:</td> <td>Pass</td> </tr> <tr> <td>Adhesion/cohesion tensile deformation properties maintained</td> <td></td> <td></td> </tr> <tr> <td style="padding-left: 40px;">in water immersion at 23°C:</td> <td></td> <td>No break</td> </tr> <tr> <td>Adhesion/cohesion tensile deformation properties maintained</td> <td></td> <td></td> </tr> <tr> <td style="padding-left: 40px;">at -30°C:</td> <td></td> <td>No break</td> </tr> </table>			Fire reaction:	Euroclass E		Water and air waterproofing:			Loss of volume	<10%		Flow resistance:	< 3mm.		Durability:	Pass	Adhesion/cohesion tensile deformation properties maintained			in water immersion at 23°C:		No break	Adhesion/cohesion tensile deformation properties maintained			at -30°C:		No break
	Fire reaction:	Euroclass E																										
	Water and air waterproofing:																											
	Loss of volume	<10%																										
	Flow resistance:	< 3mm.																										
	Durability:	Pass																										
Adhesion/cohesion tensile deformation properties maintained																												
in water immersion at 23°C:		No break																										
Adhesion/cohesion tensile deformation properties maintained																												
at -30°C:		No break																										

Note:

TECNOPOL SISTEMAS S.L.U supplies the current annex along with the DoP to make the consultancy of the CE marking easier for international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.