

DECLARATION OF PERFORMANCE

N. CPR-ES2/0030

1 Unique identification code of the product-type	TECNOFLOOR T-3020
2 Intended uses	Epoxy coating for intended use in screed and floor finishing.
3 Manufacturer	TECNOPOL SISTEMAS, S.L.U. Finlàndia, 33 08520 Les Franqueses del Vallés – Barcelona-Spain www.tecnopolgroup.com – t. +34 935682111
4 Systems of AVCP	AVCP-System 3 AVCP- System 3 (for reaction to fire)
5 Harmonized standards	EN-13813:2014
Notified bodies	LGAI TECHNOLOGICAL CENTER, SA / Applus, N. 0370 LGAI TECHNOLOGICAL CENTER, SA / Applus, N. 0370
6 Performances declared	
Essential characteristics	Performances
Reaction to fire:	Euroclass
Adherence resistance:	3,6 N/mm ²
Impact resistance:	>14,7 Nm
	At 1500 mm NO effects. Crater diameter: 4,2 mm
Wear resistance:	20µm

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by **David Pont – Technical Service Manager**

Les Franqueses del Vallés,



17/07/2023



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and the following amendments are indicated in the Safety Data Sheet that Tecnopol Sistemas S.L.U. makes available on the website along with this current Declaration of Performance.

DoP in Pdf format is available on the Tecnopol website.

<i>Revision 0 notes:</i>	<i>First issue</i>
--------------------------	--------------------

 0370, 0370	 TECNOPOL SISTEMAS, S.L.U., Finlàndia, 33 08520 Les Franqueses del Vallés – Barcelona-Spain – www.tecnopolgroup.com										
23 CPR-ES2/0030 EN-13813:2014 TECNOFLOOR T-3020 Epoxy coating for intended use in screed and floor finishing											
<table><tr><td>Reaction to fire:</td><td>Euroclass E_{fl}</td></tr><tr><td>Adherence resistance:</td><td>3,6 N/mm²</td></tr><tr><td>Impact resistance:</td><td>>14,7 Nm</td></tr><tr><td>Wear resistance:</td><td>20µm</td></tr><tr><td></td><td>At 1500 mm NO effects. Crater diameter: 4,2 mm</td></tr></table>		Reaction to fire:	Euroclass E _{fl}	Adherence resistance:	3,6 N/mm ²	Impact resistance:	>14,7 Nm	Wear resistance:	20µm		At 1500 mm NO effects. Crater diameter: 4,2 mm
Reaction to fire:	Euroclass E _{fl}										
Adherence resistance:	3,6 N/mm ²										
Impact resistance:	>14,7 Nm										
Wear resistance:	20µm										
	At 1500 mm NO effects. Crater diameter: 4,2 mm										

Note:

TECNOPOL SISTEMAS S.L.U. supplies the current annex along with the DoP to make the consultancy of the CE marking easier for international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.