

## DECLARATION OF PERFORMANCE

### N. CPR-ES2/0018

<b>1 Unique identification code of the product-type</b>	<b>TECNOFOAM G-2025</b>
<b>2 Intended uses</b>	In-situ formed sprayed rigid polyurethane foam product for thermal insulation of walls, ceilings, roofs suspended ceilings and floors.
<b>3 Manufacturer</b>	TECNOPOL SISTEMAS, S.L.U. Finlàndia, 33 08520 Les Franqueses del Vallès – Barcelona-Spain www.tecnopolgroup.com – t. +34 935682111
<b>4 Systems of AVCP</b>	AVCP-System 3
<b>5 Harmonized standards</b>	EN 14315-1:2013
<b>Notified bodies</b>	LGAI TECHNOLOGICAL CENTER, S.A/Applus N.0370 CEIS/CENTRO DE ENSAYOS, INNOVACION Y SERVICIOS N.1722
<b>6 Performances declared</b>	
<b>Essential characteristics</b>	<b>Performances</b>
Reaction to fire:	Euroclass E
Water permeability:	NPD (No Performance Determined)
Thermal resistance:	See performance chart
Water vapor permeability:	$\mu=31$
Compressive strength:	NPD (No Performance Determined)
The durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time
The durability of thermal resistance against aging/degradation:	See performance chart
The durability of compressive strength against aging/degradation:	Compressive strength does not decrease with time
Continuous glowing combustion:	NPD (No Performance Determined)

**PERFORMANCE CHART**

Closed-cell CCC2 polyurethane foam without coatings or diffusion-open surfaces.

<b>Total thickness</b>	<b>Declared aged thermal conductivity W/m-K</b>	<b>Thermal resistance level R=m<sup>2</sup> ·K/W</b>
30mm	0,033	0,90
35mm	0,033	1,10
40mm	0,033	1,20
45mm	0,033	1,40
50mm	0,033	1,50
55mm	0,033	1,70
60mm	0,033	1,80
65mm	0,033	2,00
70mm	0,033	2,10
75mm	0,033	2,30
80mm	0,033	2,40
85mm	0,033	2,60
90mm	0,033	2,70
95mm	0,033	2,90
100mm	0,033	3,00
105mm	0,033	3,20
110mm	0,033	3,35
115mm	0,033	3,50
120mm	0,033	3,60
125mm	0,033	3,80
130mm	0,033	3,95
135mm	0,033	4,00
140mm	0,033	4,25
145mm	0,033	4,50
150mm	0,033	4,60
155mm	0,033	4,70
160mm	0,033	4,90
165mm	0,033	5,00
170mm	0,033	5,20
175mm	0,033	5,30
180mm	0,033	5,50

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **David Pont – Technical Service Manager**

**Les Franqueses del Vallès,**



**01/10/2023**



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and the following amendments are indicated in the Safety Data Sheet that Tecnopol Sistemas S.L.U. makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Tecnopol website.

<i>Revision 0 notes:</i>	<i>First issue</i>
<i>Revision 1:</i>	<i>Updating tests according to the EN 14315:2013 and reaction to the fire according to the EN-13501</i>
<i>Revision 2:</i>	<i>Updating information</i>
<i>Revision 3:</i>	<i>Updating information (conductivity)</i>

 1722, 0370	 <b>TECNOPOL SISTEMAS, S.L.U., Finlàndia, 33 08520 Les Franqueses del Vallès – Barcelona-Spain – <a href="http://www.tecnopolgroup.com">www.tecnopolgroup.com</a></b>																		
<b>20</b> <b>CPR-ES2/0018</b> <b>EN 14315-1:2013</b> <b>TECNOFOAM G-2025</b> In-situ formed sprayed rigid polyurethane foam product for thermal insulation of walls, ceilings, roofs suspended ceilings, and floors																			
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;"></td> <td>Reaction to fire: Euroclass E</td> </tr> <tr> <td></td> <td>Water permeability: NPD (No Performance Determined)</td> </tr> <tr> <td></td> <td>Thermal resistance: See performance chart</td> </tr> <tr> <td></td> <td>Water vapor permeability: <math>\mu=31</math></td> </tr> <tr> <td></td> <td>Compressive strength: NPD (No Performance Determined)</td> </tr> <tr> <td>The durability of reaction to fire against aging/degradation:</td> <td>Reaction to fire does not decrease with time</td> </tr> <tr> <td style="padding-left: 20px;">The durability of thermal resistance against aging/degradation:</td> <td>See performance chart</td> </tr> <tr> <td style="padding-left: 20px;">The durability of compressive strength against aging/degradation:</td> <td>Compressive strength does not decrease with time</td> </tr> <tr> <td></td> <td>Continuous glowing combustion: NPD (No Performance Determined)</td> </tr> </table>			Reaction to fire: Euroclass E		Water permeability: NPD (No Performance Determined)		Thermal resistance: See performance chart		Water vapor permeability: $\mu=31$		Compressive strength: NPD (No Performance Determined)	The durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time	The durability of thermal resistance against aging/degradation:	See performance chart	The durability of compressive strength against aging/degradation:	Compressive strength does not decrease with time		Continuous glowing combustion: NPD (No Performance Determined)
	Reaction to fire: Euroclass E																		
	Water permeability: NPD (No Performance Determined)																		
	Thermal resistance: See performance chart																		
	Water vapor permeability: $\mu=31$																		
	Compressive strength: NPD (No Performance Determined)																		
The durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time																		
The durability of thermal resistance against aging/degradation:	See performance chart																		
The durability of compressive strength against aging/degradation:	Compressive strength does not decrease with time																		
	Continuous glowing combustion: NPD (No Performance Determined)																		

**Note:**

TECNOPOL SISTEMAS S.L.U, supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.