

DECLARATION OF PERFORMANCE

N. CPR-ES2/0024



1 Unique identification code of the product-type	TECNOFOAM G-2040HFO
2 Intended uses	In-situ formed sprayed rigid polyurethane foam product for thermal insulation of walls, ceilings, roofs suspended ceilings and floors.
3 Manufacturer	TECNOPOL SISTEMAS, S.L.U. Finlàndia, 33 08520 Les Franqueses del Vallès – Barcelona-Spain www.tecnopolgroup.com – t. +34 935682111
4 Systems of AVCP	ACVP-System 3
5 Harmonized standards	EN 14315-1:2013
Notified bodies	LGAI TECHNOLOGICAL CENTER, S.A/Aplus N.0370 CEIS/CENTRO DE ENSAYOS, INNOVACION Y SERVICIOS N.1722
6 Performances declared	
Essential characteristics	Performances
Reaction to fire:	Euroclass E
Water permeability:	Short-term water absorption by partial immersion: ≤0,10 kg/sqm
Thermal resistance:	See the performance chart
Water vapor permeability:	μ=102
Compressive strength:	NPD (No Performance Determined)
Durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time
Durability of thermal resistance against aging/ degradation:	See the performance chart; determined by an aging process
Durability of compressive strength against aging/degradation:	The compression strength does not decrease with time
Continuous glowing combustion:	NPD (No Performance Determined)

PERFORMANCE CHART

Closed-cell CCC4 polyurethane foam without coatings or diffusion-open surfaces.

Total thickness	Declared aged thermal conductivity W/m-K	Thermal resistance level R=m² ·K/W
30mm	0,028	1,10
35mm	0,028	1,30
40mm	0,028	1,40
45mm	0,028	1,60
50mm	0,028	1,80
55mm	0,028	2,00
60mm	0,028	2,10
65mm	0,028	2,30
70mm	0,028	2,50
75mm	0,028	2,70
80mm	0,026	3,10
85mm	0,026	3,30
90mm	0,026	3,50
95mm	0,026	3,70
100mm	0,026	3,80
105mm	0,026	4,00
110mm	0,026	4,20
115mm	0,026	4,40
120mm	0,025	4,80
125mm	0,025	5,00
130mm	0,025	5,20
135mm	0,025	5,40
140mm	0,025	5,60
145mm	0,025	5,80
150mm	0,025	6,00
155mm	0,025	6,20
160mm	0,025	6,40
165mm	0,025	6,60
170mm	0,025	6,80
175mm	0,025	7,00
180mm	0,025	7,20

The performance of the product identified above is in conformity with the set of declared performances.

 1722, 0370	 TECNOPOL SISTEMAS, S.L.U., Finlàndia, 33 08520 Les Franqueses del Vallès – Barcelona-Spain – www.tecnopolgroup.com																		
<p style="text-align: center;">20 CPR-ES2/0024 EN 14315-1:2013 TECNOFOAM G-2040HFO</p> <p>In-situ formed sprayed rigid polyurethane foam product for thermal insulation of walls, ceilings, roofs suspended ceilings, and floors</p>																			
<table border="0"> <tr> <td>Reaction to fire:</td> <td>Euroclass E</td> </tr> <tr> <td>Water permeability:</td> <td>Short-term water absorption by partial immersion: ≤0,10 kg/sqm</td> </tr> <tr> <td>Thermal resistance:</td> <td>See the performance chart</td> </tr> <tr> <td>Water vapor permeability:</td> <td>μ=102</td> </tr> <tr> <td>Compressive strength:</td> <td>NPD (No Performance Determined)</td> </tr> <tr> <td>Durability of reaction to fire against aging/degradation:</td> <td>Reaction to fire does not decrease with time</td> </tr> <tr> <td>Durability of thermal resistance against aging/degradation:</td> <td>See the performance chart; determined by an aging process</td> </tr> <tr> <td>Durability of compressive strength against aging/degradation:</td> <td>The compression strength does not decrease with time</td> </tr> <tr> <td>Continuous glowing combustion:</td> <td>NPD (No Performance Determined)</td> </tr> </table>		Reaction to fire:	Euroclass E	Water permeability:	Short-term water absorption by partial immersion: ≤0,10 kg/sqm	Thermal resistance:	See the performance chart	Water vapor permeability:	μ=102	Compressive strength:	NPD (No Performance Determined)	Durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time	Durability of thermal resistance against aging/degradation:	See the performance chart; determined by an aging process	Durability of compressive strength against aging/degradation:	The compression strength does not decrease with time	Continuous glowing combustion:	NPD (No Performance Determined)
Reaction to fire:	Euroclass E																		
Water permeability:	Short-term water absorption by partial immersion: ≤0,10 kg/sqm																		
Thermal resistance:	See the performance chart																		
Water vapor permeability:	μ=102																		
Compressive strength:	NPD (No Performance Determined)																		
Durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time																		
Durability of thermal resistance against aging/degradation:	See the performance chart; determined by an aging process																		
Durability of compressive strength against aging/degradation:	The compression strength does not decrease with time																		
Continuous glowing combustion:	NPD (No Performance Determined)																		

Note:

TECNOPOL SISTEMAS S.L.U, supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes