

DECLARATION OF PERFORMANCE

N. CPR-ES2/0020

1 Unique identification code of the product-type	TECNOFOAM G-2040
2 Intended uses	In-situ formed sprayed rigid polyurethane foam product for thermal insulation of walls, ceilings, roofs suspended ceilings and floors.
3 Manufacturer	TECNOPOL SISTEMAS, S.L.U. Finlàndia, 33 08520 Les Franqueses del Vallès – Barcelona-Spain www.tecnopolgroup.com – t. +34 935682111
4 Systems of AVCP	AVCP-System 3
5 Harmonized standards	EN 14315-1:2013
Notified bodies	LGAI TECHNOLOGICAL CENTER, S.A/ Applus N.0370 CEIS/CENTRO DE ENSAYOS, INNOVACION Y SERVICIOS N.1722
6 Performances declared	
Essential characteristics	Performances
Reaction to fire:	Euroclass E
Water permeability:	Short-term water absorption by partial immersion: ≤0,07 kg/sqm
Thermal resistance:	See the performance chart
Water vapor permeability:	μ=31
Compressive strength:	CS(10\Y)200
Compressive strength:	
The durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time
The durability of thermal resistance against aging/degradation:	See the performance chart
The durability of the compressive strength against aging/degradation:	Compressive strength does not decrease with time
Continuous glowing combustion:	No harmonized test method is available

PERFORMANCE CHART

Closed-cell CCC2 polyurethane foam without coatings or diffusion-open surfaces.

Total thickness	Declared aged thermal conductivity W/m-K -K	Thermal resistance level R=m² ·K/W
30mm	0,033	0,90
35mm	0,033	1,10
40mm	0,033	1,20
45mm	0,033	1,40
50mm	0,033	1,50
55mm	0,033	1,70
60mm	0,033	1,80
65mm	0,033	2,00
70mm	0,033	2,10
75mm	0,033	2,30
80mm	0,033	2,40
85mm	0,033	2,60
90mm	0,033	2,70
95mm	0,033	2,90
100mm	0,033	3,00
105mm	0,033	3,20
110mm	0,033	3,35
115mm	0,033	3,50
120mm	0,033	3,60
125mm	0,033	3,80
130mm	0,033	3,95
135mm	0,033	4,00
140mm	0,033	4,25
145mm	0,033	4,50
150mm	0,033	4,60
155mm	0,033	4,70
160mm	0,033	4,90
165mm	0,033	5,00
170mm	0,033	5,20
175mm	0,033	5,30
180mm	0,033	5,50

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by **David Pont – Technical Service Manager**

Les Franqueses del Vallès,



01/10/2023



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and the following amendments are indicated in the Safety Data Sheet that Tecnopol Sistemas S.L.U. makes available on the website along with this current Declaration of Performance.

DoP in Pdf format is available on the Tecnopol website.

<i>Revision 0 notes:</i>	<i>First issue</i>
<i>Revision 1:</i>	<i>Addition tests according to the EN 1604:2013 and EN 1607:2013</i>
<i>Revision 2:</i>	<i>Updating tests according to the EN 14315:2013 and reaction to the fire according to the EN-13501</i>
<i>Revision 3:</i>	<i>Updating information</i>
<i>Revision 4:</i>	<i>Updating information(conductivity)</i>

 1722, 0370	 TECNOPOL SISTEMAS, S.L.U., Finlàndia, 33 08520 Les Franqueses del Vallès – Barcelona-Spain – www.tecnopolgroup.com																		
<p style="text-align: center;">20 CPR-ES2/0020 EN 14315-1:2013 TECNOFOAM G-2040</p> <p>In-situ formed sprayed rigid polyurethane foam product for thermal insulation of walls, ceilings, roofs suspended ceilings, and floors</p>																			
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;"></td> <td>Reaction to fire: Euroclass E</td> </tr> <tr> <td></td> <td>Water permeability: Short-term water absorption by partial immersion: ≤0,07 kg/sqm</td> </tr> <tr> <td></td> <td>Thermal resistance: See the performance chart</td> </tr> <tr> <td></td> <td>Water vapor permeability: μ=31</td> </tr> <tr> <td></td> <td>Compressive strength: CS(10\Y)200</td> </tr> <tr> <td>The durability of reaction to fire against aging/degradation:</td> <td>Reaction to fire does not decrease with time</td> </tr> <tr> <td>The durability of thermal resistance against aging/degradation:</td> <td>See the performance chart</td> </tr> <tr> <td>The durability of the compressive strength against aging/degradation:</td> <td>Compressive strength does not decrease with time</td> </tr> <tr> <td>Continuous glowing combustion:</td> <td>No harmonized test method is available</td> </tr> </table>			Reaction to fire: Euroclass E		Water permeability: Short-term water absorption by partial immersion: ≤0,07 kg/sqm		Thermal resistance: See the performance chart		Water vapor permeability: μ=31		Compressive strength: CS(10\Y)200	The durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time	The durability of thermal resistance against aging/degradation:	See the performance chart	The durability of the compressive strength against aging/degradation:	Compressive strength does not decrease with time	Continuous glowing combustion:	No harmonized test method is available
	Reaction to fire: Euroclass E																		
	Water permeability: Short-term water absorption by partial immersion: ≤0,07 kg/sqm																		
	Thermal resistance: See the performance chart																		
	Water vapor permeability: μ=31																		
	Compressive strength: CS(10\Y)200																		
The durability of reaction to fire against aging/degradation:	Reaction to fire does not decrease with time																		
The durability of thermal resistance against aging/degradation:	See the performance chart																		
The durability of the compressive strength against aging/degradation:	Compressive strength does not decrease with time																		
Continuous glowing combustion:	No harmonized test method is available																		

Note:

TECNOPOL SISTEMAS S.L.U, supplies the current annex along with the DoP to make the consultancy of the CE marking easier for international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes